

# Hi-R-Temp<sup>®</sup> Packaged Hot Water Boilers

## SPECIFICATIONS

1,500,000 BTU/HR

### DESIGN DETAILS

#### General Information

Type of Boiler	Coiled Tube
Model Series	4242
Rated Capacity	1,500,000 Btu/hr
Water Capacity	34 gal
Construction Codes	ASME, Hartford, National Board
Boiler Shell Insulation	Mineral Wool Insulation
Approx. Shipping Weight	3,000 lbs

#### Pressure & Temperature

Pressure	Temperature
Up to 4000 psi	Up to 750° F

#### Controls

Low Combustion Air Switch, Flame Safeguard Control, Low Water Flow Switch, Coil Temperature Limit Switch, Automatic Time Delay Cooling Cycle, etc.

#### Burner

Manufacturer	Vapor Power
Fuel	Natural Gas, No. 2 Fuel Oil, or Combination
Type (gas)	Multiple Orifice Nozzle
Type (oil)	Air Atomized

#### Fuel Specifications:

Oil (No. 2)	141,000 Btu/U.S. gal
Gas	1000 Btu/cu ft
Main Burner	2 psig
Pilot Burner	6" W.C.

#### Atomizing Air Requirements:

Oil (No. 2)	5 scfm @ 40 psig
Gas	None required

#### Ignition Type:

Oil & Gas	Electric spark - interrupted gas pilot
-----------	---

#### Power Requirements

Main Power	230/460/575 VAC, 3 Ph, 60 Hz
Control Power	120 VAC, 1 Ph, 60Hz
HP required by blower	3 HP

#### Overall Dimensions

L x W x H	81" x 50" x 79"
-----------	-----------------

#### Performance Data

##### Fuel Consumption @ Rated Output

Gas	1,923 scfh
Oil (No. 2)	13.5 gal/hr

##### Turndown Ratios:

Oil & Gas	7 to 1
-----------	--------

##### Combustion and Ventilating Air Required:

Oil & Gas	485 scfm
-----------	----------

#### Customer Connections

Stack Outlet	10"	O.D.
Water Inlet	3"	Flange
Water Outlet	3"	Flange
Main Gas Supply	2"	NPT
Pilot Gas Supply	1/2"	NPT
Oil Supply	3/4"	NPT
Oil Return	1/2"	NPT
Atomizing Air	3/8"	NPT
Safety Valve Outlet	1 1/4"	NPT

-Note: varies on application details

**VAPOR POWER** INTERNATIONAL